

# Acoustic Silence 360

Datasheet - 17/03/2025



Scan Underlay®  
Upcycled Product

Specifications	Value	Tolerance
Length	25 m	+1%
Width	1 m	±2 mm
Thickness	1 mm	
Vægt	400 g	±20 g
Compressive strength (CS)	~43 ton / m <sup>2</sup> (423 kPa)	
Impact sound reduction (IS)	22 dB (EN 10140-3)	
Reflected walking sound (RWS)	51,7 Sone (EN 16354)	
Water vapour diffusion resistance (SD)	117 m	
Material	65% Rubber & 35% PP.PE.PET	

Transport	Pallet	Tower
Quantity	600 m <sup>2</sup>	1200 m <sup>2</sup>
Height	115 cm	235 cm
Width / Length	80 cm / 120 cm	

Environment	Value	Reference
French VOC Regulation	A+ <sup>(1)</sup>	
TVOC	12 µg / m <sup>3</sup> <sup>(1)</sup>	A+ <1000
PAH 8 REACH	< 15 mg / kg	< 20

 The product is suitable for underfloor heating

 The product can be included in DGNB buildings

 The product can be included in Eco-labelled buildings

1. The value is based on the product "Acoustic Silence 1050", which has a fundamentally similar material composition and production process. Therefore, it is assumed that this value is also representative of the current product.